



WINTERGLOED BV

# TECHNICAL SPECIFICATION SHEET EOE 73 mm

ED 0 DEL 10.08.2021 - REV 4 DEL 02.01.2023

## Material type :


- **Material type:** TFS-E2,8/2,8
- **Material thickness:** 0.20 mm
- **Hardness:** TH 520
- **Compound:** WATER BASED
- **Internal coating:** WHITE LAQUER 15gr.mq +/-2  
CLEAR LAQUER 5gr.mq +/-1  
or PAINTED 6gr.mq +/-1
- **External coating:** GOLDEN EPOXY 5,5gr.mq +/-0,5
- **Compound film weight:** 57 ± 5 mg
- **External cating post - repair:** MULTICOMPONENT
- **Tab:** KSTAB GOLD EXTERNAL

## Dimension:

- **Curl height CH:** 2.00 ± 0.10 mm
- **Countersink depth CD:** 4.00 ± 0.15 mm
- **Outside curl diameter OCD:** 82.00 ± 0.15 mm
- **Inside curl diameter ICD:** 73 min mm

## Mechanical performance:

- **Breack force:** 1.60 – 2.5 N/m
- **Tear force:** 3.5 – 6.5 N/m
- **Burst pressure:** 2.00 Min. bar



- **Pallet dim.(LxWxH):** 1420x1120x1280 ( mm )
- **Pallet tipe:** WOOD
- **Sleeve type:** Plastic sleeve with interleave
- **Number of ends per sleeve:** 230
- **Number of sleeve per pallet:** 474
- **Number of ends per pallet:** 109.020
- **Overpackaging:** Stretchwrap
- **Pallet weight:** 1300 Kg

Individual deliveries may have different nominal characteristics. The characteristics of the materials are always uniform for all batches of individual supplies. Other nominal values can be considered subject to prior agreement. Higher coverage than the contracted one is always allowed.